LLES & NILLES.

JAMES E. NILLES ANDREW J. NILLES JAY G. DURST LISA M. GEHRKE S. MICHAEL PATTON LINDA E.B. HANSEN

CHARLOTTE SHAPIRO THADDEUS C. STANKOWSKI MAITHEW C. LOPPNOW

REGISTERED PATENT AGENTS: LISA A. BRZYCKI MATTHEW M. ESLAMI, P.E.

INTELLECTUAL PROPERTY ATTORNEYS

FIRSTAR CENTER, SUITE 2000 777 EAST WISCONSIN AVENUE MILWAUKEE, WI 53202-5345

TELEPHONE: 414.276.0977 FACSIMILE: 414.276,0982

EMAIL: [Click here and type email]

@nilles-nilles.com

FACSIMILE TRANSMITTAL SHEET					
то:	Examiner T. Solak		FROM:	James E. Nilles	
COMPANY:	US Patent and Trademark Office		DATE:	April 30, 2001	
FAX NO.:	703.308.7763		PAGES:	7 (Including Cover Sheet)	
RE:	09/541,779		OPERATOR:	A. Weinstock	
☐ Original Will Follow ☐ Original Will Not I		ollow Buclosures Will Follow With Original			
☐ Urgent	☐ For Review	w	comment	☐ Please Reply	☐ Please Recycle

NOTES:

OPY RECEIVED

RAPR 5 2001

GROUP 3400





I hereby certify that this correspondence is being sent by facsimile to telephone number: 703.308.7763 on April 30, 2001 to Examiner T. Solpk at the United States Patent and Trademark Office.

Angela Weinstock

April 30, 2001 Date

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Hisatoshi HIROTA

Art Unit:

Not Known

Application No.:

09/541,779

Examiner:

Solak

Filing Date:

April 3, 2000

Docket No.: 133,046

For:

CAPACITY CONTROLLER OF CAPACITY VARIABLE

COMPRESSOR

PRELIMINARY AMENDMENT

Commissioner of Patents and Trademarks Washington, D.C. 20231

Sir:

This Preliminary Amendment is directed to the new U.S. application as identified above. Please enter this preliminary amendment prior to calculating the fees and amend the application as follows:

IN THE CLAIMS

Please cancel claims \dot{A} -9 without prejudice and add the following new claims:

10. (New) A variable capacity controller of a compressor comprising:

a pressure controlled capacity variation mechanism connected to the solenoid actuated capacity controller generating a variable control pressure for the mechanism on the basis of an initial value of an inhalation pressure of the compressor;

wherein the capacity controller includes a valve seat located between a first valve chamber part and a second valve chamber part, and a piston actuated valve closure part to open or close communication between a differential pressure port connected to a control

